

**BANNER FLEX DE 10 ONZ (300 D - 200 D X 300 D)**

ITEM	VALUE	UNIT	TEST METHOD
fabric	(usual tenacity yarns) 100%PES(200d*300d)		DIN EN ISO2060
construction	18*12 Warp knitting 18*12	INCH	DIN60001
weight of fabric (Peso de la tela)	43	<u>gsm</u>	DIN53352 BS3424method5B
weight of pvc laminated (peso del pvc laminado)	257	<u>gsm</u>	DIN53352 BS3424 method5B
breaking strength	warp: 497 weft: 301	N/SCM	DIN53354 BS3424method6A
tear strength	warp: 85 weft: 65	N	DIN53356 BS3424method7A
adhesion	50	N/SCM	DIN53357 BS3425 method9B
suitable temperature	-10 -----+70	°C	DIN53357 BS3425 method10
Lacquering	IF the clients need ,we can reach:3555(Acrylic), 3483(Acrylic),7584(PVDF)		
Flammability	If the clients need, products can reach :DIN75200,B1,B2,NFPA701		
Cd% ,Pb% ,As% ,Ba% , Cr% ,Hg% ,Se%	If the clients need, we can reach EN71-3: Cd% <100ppm,Pb%<90ppm,As%<25ppm,Ba%<1000ppm Cr%<60ppm,Hg%<60ppm,Se%<500ppm		

¡Pégate a nosotros!

ADH